

TYPE/HARDWARE HOLLOW METAL DOOR LEVER HARWARE STORE FRONT DOOR WITH PANIC HARDWARE O.H. GARAGE DOOR HOLLOW METAL WITH LEVER HARDWARE SOLID METAL WITH PANIC HARDWARE HOLLOW METAL WITH LEVER HARDWARE TO BE

	<u>D</u>	(E) / (N)	<u>SIZE</u>	<u>REMARKS</u>
	A	(E)	5'-0" x 3'-0"	-
	В	(E)	7'-0"x 6'-8"	ı
	(c)	<i>(</i> ⊨)	6'-2" × 5'-0"	_

- A. DEADBOLTS ARE NOT PERMITTED ON EXIT DOORS. A DURABLE SIGN WITH I" HIGH LETTERS SHALL BE PLACED OVER ALL EXIT DOORS STATING THAT "THIS DOOR TO
- B. ALL EXITS TO BE OPENABLE FROM INSIDE WITHOUT USE OF A
- C. ALL DOOR HARDWARE SHALL BE PUSH TYPE OR PANIC BAR
- D. ALL GLASS OVER 9 SQ. FT. IN AREA WITHIN 18" OF FLOOR OR 36" OF GRADE, AND ALL GLASS DOORS AND WALL
- E. LOCK AND LATCH IS ALLOWED ONLY IF THEY COMPLY WITH CBC 1010.19.3 PANIC HARDWARE SHALL COMPLY WITH CBC
- F. WHEN ADDITIONAL DOORS ARE PROVIDED, THEY SHALL CONFORM TO THE PROVISIONS FOR EXIT DOORS CBC 1010.1
- G. LANDING OR FLOOR LEVEL AT DOORS SHALL NOT BE LESS THAN 1 INCH. RAISED THRESHOLDS AND FLOOR LEVEL CHANGES GREATER THAN 1 INCH AT THE DOORWAYS SHALL BE BEVELED WITH A SLOPE NOT GREATER THAN ONE UNIT VERTICAL IN TWO UNITS HORIZONTAL.CBC 1008.1.7.
- H. DOOR SWINGING OVER LANDING SHALL NOT REDUCE THE WIDTH BY MORE THAN SEVEN INCHES WHEN FULLY OPEN. WHEN SERVING 50 OR MORE PEOPLE THE DOOR IN ANY POSITIONS SHALL NOT REDUCE THE REQUIRED WIDTH TO LESS THAN ONE-HALF. DOOR IN FULLY OPENED POSITION SHALL NOT REDUCE A REQUIRED LANDING DIMENSION BY MORE THAN 7

EXIT WAYS SHALL BE ILLUMINATED WITH AT LEAST ONE FOOT CANDLE AT THE FLOOR LEVEL PER CBC 1008.2 \$ 1008.3

- MIN. DOOR STRIKE EDGE DISTANCE OF 24" @ EXTERIOR DOORS, 12" ON THE
- MAX. HEIGHT OF THRESHOLD SHALL BE 1/2" WITH MAX SLOPE OF 1:12.
- DOOR OPENING FORCE APPLIED TO THE LATCH SIDE SHALL NOT EXCEED THE
- 4. ALL DOOR OPENINGS SHALL BE MINIMUM 32" CLEAR WITH DOOR OPEN @ 90°.
- 6. ALL HAND-ACTIVATED DOOR OPENING HARDWARE MEETS THE FOLLOWING
 - A. LATCHING, OR LOCKING DOORS IN A PATH OF TRAVEL ARE OPERATED WITH A SINGLE EFFORT BY LEVER TYPE HARDWARE, BY PANIC BARS, PUSH-PULL ACTIVATING BARS, OR OTHER HARDWARE DESIGNED TO PROVIDE PASSAGE WITHOUT REQUIRING THE ABILITY TO

NEW MALL	
EXIST'S WALL TO REMAIN	
EXIST'S WALL TO BE REMOVED	

- CONTRACTORS AND SUBCONTRACTORS SHALL VERIFY ALL DIMENSIONS IN
- PRIOR TO STARTING CONSTRUCTION AND NOTIFY ARCHITECT OF ANY
- 3.I. ALL STUDS SHALL BE STUD GRADE 2X6 @ 16" O.C. 2X6 AT PLUMBING
- FRAMING LUMBER SHALL BE AS FOLLOWS:
- STUD STUD GRADE JOISTS AND RAFTERS NO, 2DF
- BEAMS AND HEADERS NO. I DF

DRAWN: Y.LEMUS 1910

DATE: 07/24/19

SCALE:

REVISIONS

DATE:

URI

 \propto

REN,8-31-19

DATE: 02/07/2019

DATE: PHASE

7/24/19

SUBMITTALS

7/24/19 Building & Saitey_

Planning_l

JACINTO LN,
LOCATED AT:
24200 Sunnymead P
Moreno Valley, C

 \Box